



# Material Safety Data Sheet

Product name: **STRUCTOVIS AHD (#016001)**

Date: May 20, 2003

Replaces: August 1998

Page: 1 of 3

---

## Section 1 - Product and Company Identification

Company: Klüber Lubrication North America L.P.

32 Industrial Dr.  
Londonderry, N.H. 03053  
Phone: (603) 647-4104

Emergency telephone #: 1-800-424-9300 (Chemtrec)  
Fax: (603) 647-4105

Product Use: Lubricating oil.

---

## Section 2 - Composition/Information on Ingredients

<b>Ingredients</b>	<b>TLV</b>	<b>PEL</b>
Paraffin basic mineral oil	N/A	N/A
Synthetic hydrocarbon oil	N/A	N/A
Special additives on the base of barium petroleum sulfonate	N/A	N/A

---

## Section 3 - Hazards Identification

**Eye Contact:** May cause mild irritation upon immediate contact.

**Skin contact:** Prolonged or repeated contact may cause the removal of skin oils, possibly leading to irritation or dermatitis.

**Inhalation:** Vapor inhalation under ambient conditions will not occur. Vapor pressure is very low. The inhalation of vapors (generated at extremely high temperature only) or oil mist may cause a mild irritation of the mucous membranes of the upper respiratory tract. Harmful concentrations of mists and/or vapors are unlikely to occur through reasonable and customary use of this product.

**Ingestion:** No acute or chronic effects expected. However, minute amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury.

---

## Section 4 - Emergency and First Aid Procedures

**After contact with eyes:** Flush eyes with plenty of water for 15 minutes. If irritation persists, or if an infection develops, seek medical attention.

**After contact with skin:** Wash off with soap and plenty of water. Apply skin cream if necessary. Seek medical attention if irritation or infection occurs. Remove contaminated clothing and wash before reuse.

**After inhalation:** If overcome by product vapor heated to extreme temperatures, immediately move from exposure and get medical attention. If breathing is irregular, start resuscitation or administer oxygen if available. If overexposed to oil mist, remove from further exposure until excessive oil mist condition subsides.

**After ingestion:** If large amounts are swallowed, do not induce vomiting. Get medical attention.

**Advice to doctor:** Treat symptomatically.

---

## Section 5 - Exposure Controls

**Eye protection:** Wear safety goggles if splashes may occur. Do not wear contact lenses when using chemicals.

**Hand protection:** Wear chemical resistant gloves.

**Body protection:** Wear clean, body-covering clothing to minimize dermal exposure.

**Ventilation:** Under normal conditions of use, no special ventilation is required. However, if vaporized or misted and limits in Section 2 are exceeded, use local exhaust.

**Respiratory protection:** No special respiratory protection is required. However, if product is overheated beyond conditions of normal use, or misted, and the limits in Section 2 are exceeded, wear the appropriate NIOSH-approved respiratory protection.

**Other protection measures:** Safety showers, eye wash fountains, and washing facilities should be readily available.



# Material Safety Data Sheet

Product name: **STRUCTOVIS AHD (#016001)**

Date: May 20, 2003

Replaces: August 1998

Page: 2 of 3

---

## Section 6 - Fire Fighting Measures

**Flash point:** Approx. 250°C Method Used: ASTM D 92

**Lower explosion limit:** N/Av

**Upper explosion limit:** N/Av

**Extinguishing media:** Water spray, foam, dry powder, carbon dioxide (CO<sub>2</sub>)

**Unusual fire and explosion hazards:** Empty metal containers retain product residue. Do not pressurize, cut, weld, drill, solder or expose container to heat, flame, sparks, or other sources of ignition: it may explode, causing serious injury or death. Exposure to heat builds up pressure in container. Cool with water spray.

**Special fire Fighting Procedures:** If leak or spill has not ignited, use water spray to disperse any vapor and to flush spills away from ignition sources. Use self-contained breathing apparatus for enclosed or confined spaces or as otherwise needed. Do not use direct stream of water, material may float and re-ignite.

---

## Section 7 - Accidental Release Measures

If product leaks or is inadvertently spilled, eliminate ignition sources isolate surrounding spill area with the proper containment system to prevent the spill from reaching waterways. Add absorbent and soak up the product. Collect product and absorbent, place in a chemical waste container for proper disposal.

---

## Section 8 - Handling and Storage

Avoid contact with skin and remove soiled or soaked clothing. Wash hands with soap and water before eating, drinking, and/or smoking. Clean skin thoroughly after work and if necessary, apply skin cream.

Store product under normal temperature and pressure.

Store product away from heat sources and food products.

---

## Section 9 - Physical and Chemical Properties

**Boiling Point:** N/Av

**Vapor Pressure (mm Hg.):** N/Av

**Vapor Density ( air = 1 )::** N/Av

Method: DIN 51757

**Solubility in Water:** Insoluble

**Specific Gravity (H<sub>2</sub>O = 1):** 0.91

**Evaporation rate (ether = 1):** N/Av

**Appearance and odor:** Light brown liquid with a neutral odor

---

## Section 10 - Stability and Reactivity

**Stability:** Stable

**Conditions to avoid:** Open flames and other sources of heat

**Materials to avoid:** Strong oxidizing agents such as pure oxygen

**Hazardous decomposition products:** Fumes, smoke, carbon monoxide and carbon dioxide.

**Hazardous polymerization:** Will not occur

---



# Material Safety Data Sheet

Product name: **STRUCTOVIS AHD (#016001)**

Date: May 20, 2003

Replaces: August 1998

Page: 3 of 3

---

## Section 11 - Toxicological Information

Acute toxicity: N/Av for this product.

Chronic toxicity: N/Av for this product.

---

## Section 12- Disposal Considerations

Under RCRA, it is the user's responsibility to determine, at the time of disposal, whether the product meets any of the criteria for a hazardous waste defined in 40 CFR 261. As a new product it would not be considered RCRA hazardous waste.

---

## Section 13- Transportation Information

Proper Shipping Name	Hazard Class or Division	UN ID	Packing Group
N/Av			

---

## Section 14 – Regulatory Information

All product components comply with all applicable rules and orders under the Toxic Substance Control Act (TSCA).

Barium compounds are subject to the release reporting requirements under SARA Title III, section 313. This product contains 2% barium compound. Please refer to the appropriate regulations for proper compliance.

---

## Section 15 - Additional Information

HMIS Rating: Health -1    Flammability - 1    Reactivity - 0    Personal Protection - B

Unk. = Unknown    N/Av = Not Applicable    N/Av = Not Available    ~ = Approximately

---