




Straight Pinions,

milled teeth, 20° pressure angle, C45 (AISI 10L45)



Quality
8 e 25
(~AGMA 10)

Order code	Module m	No of teeth z	d	d _k	d ₁	d _N	b ₁	b ₂	Wt. (lb)
5 mm Circular Pitch									
07 06 012	1.591	12	19.1	22.3	6	14	12	25	0.066
07 06 015	1.591	15	23.9	27.0	6	18	12	25	0.132
07 06 018	1.591	18	28.6	31.8	8	20	12	25	0.154
07 06 020	1.591	20	31.8	35.0	8	20	12	25	0.220
07 06 025	1.591	25	39.8	43.0	8	25	12	25	0.308
07 06 030	1.591	30	47.7	50.9	10	30	12	25	0.440
07 06 040	1.591	40	63.6	66.8	10	40	12	25	0.792
07 06 050	1.591	50	79.6	82.7	12	50	12	25	1.232
07 06 060	1.591	60	95.5	98.6	12	60	12	25	1.804
10 mm Circular Pitch									
07 08 012	3.183	12	38.2	44.6	10	25	25	40	0.484
07 08 015	3.183	15	47.7	54.1	12	30	25	40	0.836
07 08 018	3.183	18	57.3	63.7	15	40	25	40	1.100
07 08 020	3.183	20	63.7	70.0	15	40	25	40	1.320
07 08 025	3.183	25	79.6	85.9	15	50	25	40	2.110
07 08 030	3.183	30	95.5	101.9	20	60	25	40	3.210
07 08 040	3.183	40	127.3	133.7	20	80	25	40	5.900

Additional machining (boring, adding keyway, threading, etc.) is possible with quick turn around time.