

Helical-Tooth Pinion, 19° 31' 42" left-hand, splined bore

16MnCr5, 1.7131

Carborized & Hardened

Quality 5 e 24

With washer and screw DIN 7991

Screw Size	Strength Class	Tightening Torque (Nm)
M5	10.9	7
M8	8.8	20
M12	8.8	68
M16	8.8	168
M20	8.8	340

Order Code	N° of Teeth	Module	Profile Modification		Fu Tab.	d	d _{wz}	dk	d1	L	d2	L1	L2	b	M	Spline, Soft DIN 5480 *	kg
			Factor x														
79 11 538	38	1.5	-	6.8	60.48	60.48	63.48	30	33	24	12	27.5	20	M8x25	N22x1.25x30x16x7H	0.1	
79 20 515	15	2	0.5922	4.5	31.83	34.20	38.0	24	32	18	11	26.5	26	M5x16	N16x0.8x30x18x7H	0.2	
79 20 516	16	2	0.6117	4.5	33.95	36.40	40.1	24	32	18	11	26.5	26	M5x16	N16x0.8x30x18x7H	0.2	
79 20 518	18	2	0.5000	4.5	38.20	40.20	44.0	24	32	18	11	26.5	26	M5x16	N16x0.8x30x18x7H	0.3	
79 21 518	18	2	0.5000	6.8	38.20	40.20	44.0	30	33	24	12	27.5	26	M8x25	N22x1.25x30x16x7H	0.3	
79 21 520	20	2	0.4900	6.8	42.44	44.40	48.2	30	33	24	12	27.5	26	M8x25	N22x1.25x30x16x7H	0.3	
79 21 522	22	2	0.4786	6.8	46.69	48.60	52.5	30	33	24	12	27.5	26	M8x25	N22x1.25x30x16x7H	0.4	
79 21 525	25	2	-	6.8	53.05	53.05	57.05	30	33	24	12	27.5	26	M8x25	N22x1.25x30x16x7H	0.4	
79 22 523	23	2	0.4981	19.0	48.81	50.80	54.6	40	34	35	13	27.0	26	M12x35	N32x1.25x30x24x7H	0.4	
79 22 525	25	2	0.4871	20.0	53.05	55.00	59.0	40	34	35	13	27.0	26	M12x35	N32x1.25x30x24x7H	0.4	
79 22 527	27	2	0.3760	20.0	57.30	58.80	62.6	40	34	35	13	27.0	26	M12x35	N32x1.25x30x24x7H	0.5	
79 33 520	20	3	0.4563	28.5	63.66	66.40	72.2	50	51	41	20	41.0	31	M16x45	N40x2x30x18x7H	0.7	
79 33 522	22	3	0.4620	29.5	70.03	72.80	78.6	50	51	41	20	41.0	31	M16x45	N40x2x30x18x7H	0.8	
79 33 524	24	3	0.4676	29.5	76.39	79.20	85.0	50	51	41	20	41.0	31	M16x45	N40x2x30x18x7H	1.0	
79 44 520	20	4	0.4000	54.0	84.88	88.08	96.1	75	54	56	20	44.0	41	M20x50	N55x2x30x26x7H	1.5	
79 45 525	25	4	0.3400	57.5	106.10	108.82	116.8	90	65	72	24	55.0	41	M20x50	N70x2x30x34x7H	3.0	

* Put MoS2-powder or suitable grease in spline area to reduce micro corrosion

Calculation of center distance 'a' between pinion and rack

